

Foundations on Expansive Clay Soil Part 3 - Investigation of Failed Foundations



Presented by:
Eric Green, P.E.
Structural Engineer

Slide 1

Copyright Eric Green 2005

Investigation of Foundation Failure

- Is structure moving?
- Where is movement occurring?
- Is structure experiencing heave, settlement or a combination?
- Is movement excessive?
- Why is movement occurring?
- What (if any) remedial measures are required?

Slide 2

Copyright Eric Green 2005

Investigation Steps

- Data Collection
- Testing
- Interpretation
- Recommendations

Slide 3

Copyright Eric Green 2005

Step 1 - Data Collection



Slide 4

Copyright Eric Green 2005

Review of Construction Documents

- Civil, structural and landscaping plans
- Original geotechnical report
- Compaction reports
- Fill testing
- Time of construction
- Reports by other consultants

Slide 5


Copyright Eric Green 2005

Field Investigation

- Elevation survey of slab
- Distress survey (interior and exterior)
- Leak testing of plumbing lines
- As-built structural documentation
- Geotechnical investigation
- Topographic/drainage survey
- Vegetation survey
- Owner interview

Slide 6

Copyright Eric Green 2005



Elevation Survey

Slide 7

Copyright Eric Green 2005

Elevation Survey

- Most important investigation tool.
- Normally done with digital water level.
- Adjust for thickness of floor coverings.
- Floors are not constructed flat. Differential elevation does not equal differential movement.
- Multiple surveys over time are useful where possible.

Slide 8

Copyright Eric Green 2005

Distress Survey - Interior

- Map locations and type of interior distress.
 - Separation vs. crack
 - Orientation & locations
 - Width & pattern
 - Photos
- Door alignment in frame & adjusted door strikes.
- Previous repairs to structure

Slide 9

Copyright Eric Green 2005

Finish crack



Slide 10

Copyright Eric Green 2005


Finish Cracks



Slide 11

Copyright Eric Green 2005

Finish Separations



Slide 12

Copyright Eric Green 2005

Door Alignment



Slide 13

Copyright Eric Green 2005

Door Alignment



Slide 14

Copyright Eric Green 2005

Prior Repairs to Finishes



Slide 15

Copyright Eric Green 2005


Interior Underpinning



Slide 16

Copyright Eric Green 2005


Slab & Tile Cracks



Slide 17

Copyright Eric Green 2005

Interior Distress Map



Slide 18

Copyright Eric Green 2005


Distress Survey - Exterior

- Map location and type of exterior distress.
 - Crack vs separation
 - Orientation
 - Width & pattern
 - Photos
- Movement in adjacent flat work.
- Age

Slide 19

Copyright Eric Green 2005

Finish Cracks



Slide 20

Copyright Eric Green 2005


Finish Separations



Slide 21

Copyright Eric Green 2005

Previous Repairs to Finishes



Slide 22

Copyright Eric Green 2005

Previous Repairs to Finishes



Slide 23

Copyright Eric Green 2005

Differential Movement at Pier Caps



Slide 24

Copyright Eric Green 2005

Movement of Flat Work



Ramp

Slide 25

Copyright Eric Green 2005

Movement of Flat Work



Slide 26

Copyright Eric Green 2005

Previous Underpinning



Slide 27

Copyright Eric Green 2005

A/C Condensate Drain



Slide 28

Copyright Eric Green 2005


Cracking of Exposed Slab



Slide 29

Copyright Eric Green 2005

Exterior Distress Map



Slide 30

Copyright Eric Green 2005


Sewer Line Leak Testing

- Tested for leaks under hydrostatic pressure using inflatable plugs to isolate lines. Water level is observed from toilet or other fixture.
- Leakage under operational conditions can be determined using flow test.
- Video cameras can be used to examine condition of sewer lines and geometry of leaks.

Slide 31

Copyright Eric Green 2005

Hydrostatic Leak Testing



Slide 32

Copyright Eric Green 2005

Leak Test Limitations

- Systems which leak under hydrostatic pressure may not leak in operation.
- Testing cannot reliably locate multiple leaks in the same branch. Some areas cannot be tested due to lack of access.
- Flow test results may not match hydrostatic test results.

Slide 33

Copyright Eric Green 2005


Leak Test Limitations

- Small leaks may not be detected in flow testing.
- Flow testing may not replicate actual flow conditions during operation.
- Soil saturation from hydrostatic test may affect flow test results.

Slide 34

Copyright Eric Green 2005

Multiple Leaks



Slide 35

Copyright Eric Green 2005

As-Built Construction

- Check for piers using soil probe. If piers are present, excavate to determine if piers are original or remedial.
- Check pier depth and bell size.
- Check for voids and void boxes under grade beams and slab.
- Check depth of grade beam.
- Locations of expansion joints.

Slide 36

Copyright Eric Green 2005


As-Built Construction

- Concrete compressive strength
- Slab reinforcing (size, spacing and depth).

Slide 37

Copyright Eric Green 2005


Pier Excavation



Slide 38

Copyright Eric Green 2005


Gap at Pier Cap



Slide 39

Copyright Eric Green 2005

The Wrong Way



Slide 40

Copyright Eric Green 2005

Test Pits

Test pits dug along grade beams can reveal significant information:

- Depth of grade beam.
- Presence/absence of void boxes.
- Voids grade beams.
- Presence of piers.
- Separation between pier and grade beam.
- Water under slab.
- Type of fill at perimeter (clay vs loam).

Slide 41

Copyright Eric Green 2005

Geotechnical Investigation

- Soil moisture profile (water content, liquidity index and/or suction).
- Soil classification.
- Depth and type of fill.
- Swell potential/plasticity index.
- Depth to water table.
- Interior, adjacent and remote (baseline) borings.

Slide 42

Copyright Eric Green 2005

Geotechnical Investigation

- Design data
 - Allowable bearing pressure for piers
 - Potential vertical rise
 - Expected consolidation under design loads.

Slide 43

Copyright Eric Green 2005

Petrography

- Testing conducted on cores recovered in interior geotechnical borings.
- Shrinkage vs stress crack
- Plastic shrinkage cracking
- w/c ratio

Slide 44

Copyright Eric Green 2005

Test Pits

- Depth of grade beams.
- Presence of voids or void boxed under grade beams.
- Water under foundation.
- Presence of piers.
- Separations between piers and grade beams.

Slide 45

Copyright Eric Green 2005

Drainage Survey

- Micro slope adjacent to building.
- Locations of downspouts and splash blocks.
- Drainage of flower and shrub beds, including drainage plane.
- Areas of negative drainage.

Slide 46

Copyright Eric Green 2005

Improper Surface Drains



Gap between
downspout and drain

Slide 47

Copyright Eric Green 2005

Trapped Drainage



Trapped by
Sidewalk

Slide 48

Copyright Eric Green 2005

Trapped Drainage



Flowerbed Traps
Surface Drainage

Slide 49

Copyright Eric Green 2005


Pool MEP



Slide 50

Copyright Eric Green 2005

Perched Drainage Plane



Slide 51

Copyright Eric Green 2005

Landscaping Survey

- Location, type and sizes of large trees.
- Extent of tree canopies.
- Gaps between soil and grade beams.
- Locations of shrub and flower beds.
- Locations of sprinkler heads.
- Location of concrete and impermeable flatwork.

Slide 52

Copyright Eric Green 2005

Soil Gaps at Grade Beam



Slide 53

Copyright Eric Green 2005

Gap Under Grade Beam



Slide 54

Copyright Eric Green 2005

Dessicated Soil



Slide 55

Copyright Eric Green 2005

Dessicated Soil



Slide 56

Copyright Eric Green 2005

Trees



Slide 57

Copyright Eric Green 2005

Owner Interview

- History of foundation movement.
- Timing of distress.
- Sequence of distress.
- Cyclical/seasonal movement of cracks.
- Plumbing problems.
- Irrigation practices.

Slide 58

Copyright Eric Green 2005

Structural Monitoring

- Monitoring over time can help to determine cause of distress and appropriate repair methodology.
- Crack widths can be monitored with crack gage.
- Ensure elevation measurements are taken at the same locations.
- Use permanent external benchmark if possible

Slide 59

Copyright Eric Green 2005


Crack Gage



Slide 60

Copyright Eric Green 2005

Crack Measurement



Slide 61

Copyright Eric Green 2005

Step 2 - Data Analysis

- The information gathered in the data collection phase must tell a consistent story.
- No single source of data can be used to determine magnitude, mode or cause of movement.

Slide 62

Copyright Eric Green 2005


Failure Patterns

- Center heave (also called doming, hogging or center lift).
- Edge settlement
- Center settlement
- Edge heave (also called edge lift)
- Slope creep (typically on slopes greater than 5%)

Slide 63

Copyright Eric Green 2005


Types of Movement



Slide 64

Copyright Eric Green 2005


Center Heave/Edge Settlement



Slide 65

Copyright Eric Green 2005


Edge Settlement



Slide 66

Copyright Eric Green 2005

Edge Heave/Center Settlement



Slide 67

Copyright Eric Green 2005

Causes of Foundation Movement

- Variation in climate.
- Change in depth of water table.
- Removal of trees.
- Planting of trees
- Inadequate drainage.
- Seepage along construction interfaces.
- Irrigation

Slide 68

Copyright Eric Green 2005

Causes of Foundation Movement

- Leaking utility lines
- Drying of soil below heated rooms
- Seepage of moisture along utility trenches
- Poor compaction of fill.
- Improper fill material.

Slide 69

Copyright Eric Green 2005

Interpretation of Differential Elevation Survey

- Slabs are not poured perfectly level.
- Is differential elevation movement of as-built condition?
- ACI tolerance for slab on grade is $\pm 3/4$ " from nominal elevation.
- F-number gives allowable tilt. For bull-floated slab, maximum local tilt ranges from 0.9% to 1.0%.

Slide 70

Copyright Eric Green 2005

Geotechnical Interpretation

- Existing vs pre-construction MC and LI .
- MC and LI at high and low areas.
- Existing vs pre-construction bearing strength.
- MC and LI at leak and remote.
- MC and LI at interior and perimeter.

Slide 71

Copyright Eric Green 2005

Interpretation of Field Data

- Are voids

Slide 72

Copyright Eric Green 2005

Design Review

- Soil shrink-swell or soil failure under loads?
- Design analysis vs. failure analysis.
- Service loads on piers vs. allowable loads.
- Bearing pressure under grade beams.
- Bearing pressure under full foundation area.

Slide 73

Copyright Eric Green 2005

Analysis of Cracks


- Not all cracks are caused by foundation movement.
 - Differential Movement (shear & flexural stress).
 - Thermal cracking (axial stress).
 - Moisture changes (axial stress).
- Rigid finishes are more susceptible to movement.
- Distress must be consistent with differential movement.

Slide 74

Copyright Eric Green 2005

Shear Cracks due to Differential Movement


- Diagonal cracks in walls are generally due to differential movement.
- Diagonal cracks form at location of maximum principle stress (tension).
- Vertical cracks in walls are generally due to thermal movement..
- Cracks due to expansive soil move generally show cyclical movement to some extent.
- Direction of diagonal crack can show direction of relative motion but not direction of absolute motion.



Slide 75

Copyright Eric Green 2005

Shear Cracks due to Differential Movement



Slide 76

Copyright Eric Green 2005

Flexural Cracks due to Differential Movement

- Flexure of the slab can result in vertically oriented cracking of finishes.
- These cracks will be tapered (wider at the top or bottom) depending on the mode of movement (center lift or edge lift).

Slide 77

Copyright Eric Green 2005

Thermal Cracking

- Can be mistaken for cracking caused by differential movement.
- Thermal movement in masonry (Brick and CMU) results in uniform width vertical cracks due to axial stresses.
- Cracks tend to occur at openings and changes in wall alignment.
- Absence of expansion joints will increase probability of thermal cracks.

Slide 78

Copyright Eric Green 2005

Thermal Cracking Rates (No Differential Movement)




Figure 13-2 Cracking rates for masonry structures at Mercury, Nevada. Dots represent inspection dates. (From Wall, 1966.)

Slide 79

Copyright Eric Green 2005

Thermal Crack



Slide 80

Copyright Eric Green 2005

Thermal Crack



Slide 81

Copyright Eric Green 2005

Thermal Crack



Slide 82

Copyright Eric Green 2005

General Analysis of Cracks

- All structures have cracks.
- Distress should be worse in area exhibiting movement.
- Direction of relative movement should be consistent with differential elevation survey and cause of movement.

Slide 83

Copyright Eric Green 2005

Cracking of Slab

- Slab cracking without vertical displacement across the crack is rarely a result of differential movement.
- Common causes of slab cracks:
 - Drying shrinkage
 - Plastic shrinkage
 - Restraint to shrinkage
 - Excess w/c ratio
 - Inadequate control joints or slab steel

Slide 84

Copyright Eric Green 2005

Drying Separations

- Separations in wood trim and minor cracking of drywall finishes can be a result of drying of wood framing and/or trim.

Slide 85

Copyright Eric Green 2005

Drying Separations



Slide 86

Copyright Eric Green 2005

Timing of Failure

The probability of foundation failure increases with time:

- Vegetation increases in size.
- Probability of experiencing extreme drought or extreme precipitation increases.
- Probability of a failure in utility systems increases (water and sewer lines).

Slide 87

Copyright Eric Green 2005


Climate Review

- A review of the climate records is useful in determining the mode of movement (heave vs. settlement).
- Heave can be associated with periods with above average rainfall and/or below average temperatures.
- Settlement tends to be associated with periods of below average rainfall and above average temperature

Slide 88

Copyright Eric Green 2005

Houston Area Precipitation (IAH Data)



Slide 89

Copyright Eric Green 2005

Plumbing Leaks

- Sewer leaks can result in localized heave of the foundation.
- Sewer leaks rarely cause significant movement.
 - Impermeability of clay prevents water migration over wide area.
 - Leaks are not pressurized.
- Leaks can be caused by movement; chicken and egg problem.

Slide 90

Copyright Eric Green 2005

Plumbing Leaks

- Leaks in riser can migrate through sand bed and/or plumbing trench.
- Grade beams act as barrier to migration through sand bed.

Slide 91

Copyright Eric Green 2005

Plumbing Leaks and Settlement

- Plumbing leaks can cause settlement via two mechanisms:
 - Liquification of soil (loss of bearing strength)
 - Erosion.
- These phenomena are rarely seen in practice.

Slide 92

Copyright Eric Green 2005

Need for Repairs

- There is no generally accepted criteria to determine when repairs to a foundation are needed.
- All slab-on-ground structures will experience some movement.
- All slab-on-ground structures will experience some cosmetic cracking of finishes.

Slide 93

Copyright Eric Green 2005

Need for Repairs

- Considerations for recommending repairs include:
 - The owners performance expectations.
 - The owners economic sensitivity (cost of repairs vs. cost of maintenance).
 - Potential for future movement.
 - Life safety (rarely an issue).
 - Effectiveness of repairs.

Slide 94

Copyright Eric Green 2005