

Paid \$65 July 9, 2015

[CL](#) denver > for sale > materials - by owner

Posted: 15 days ago

**YOLO Colorhouse Paint For Sale Color White - \$75**

4 1Gallon YOLO COLORHOUSE paint, not open.  
ZERO VOC Base  
Color : Bisque.01(White)


Retail price: \$36.95 per Gallon

Total \$75 / OBO

Pick up in LAKewood available

Cash only

- do NOT contact me with unsolicited services or offers

condition: **new**make / manufacturer: **Yolo Colorhouse**model name / number: **Bisque.01**



# MATERIAL SAFETY DATA SHEET

Colorhouse® Inspired Multi-Purpose Primer, Flat, Eggshell, and Semi-Gloss

**Emergency telephone number:** 1-800-535-5053 US/Canada (INFOTRAC)

**Distributed by:** Colorhouse, 519 NE Hancock #B, Portland, OR 97212, 503-493-8275

The following Material Safety Data Sheet (MSDS) is being provided pursuant to requirements of the Fed/OSHA (29 CFR 1910.1200) and Cal/OSHA (8 CCR 5194) Hazard Communication Standards.

The health and hazards information given here is based on data believed to be accurate by YOLO Colorhouse LLC; we do not, however, assume any liability for the accuracy or completeness of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones that may exist. All persons intending to rely on any recommendation, or to use any technique, equipment, or material mentioned should first satisfy themselves that they can meet all applicable safety and health standards.

As permitted by OSHA, each MSDS may apply to a class of products which have similar hazards and contents.

## Product list:

1411xx Colorhouse Inspired Flat White  
1421xx Colorhouse Inspired Flat Medium  
1441xx Colorhouse Inspired Flat Neutral  
1412xx Colorhouse Inspired Eggshell White  
1422xx Colorhouse Inspired Eggshell Medium  
1442xx Colorhouse Inspired Eggshell Neutral  
1413xx Colorhouse Inspired Semi-Gloss White  
1423xx Colorhouse Inspired Semi-Gloss Medium  
1443xx Colorhouse Inspired Semi-Gloss Neutral  
1404xx Colorhouse Inspired Multi-Purpose Primer

## 1 - IDENTIFICATION

**Product code:** (See product list above)

**Product name:** Colorhouse Inspired

**Product type:** Waterborne Paint

**Product use:** Interior

**HMIS codes:** H F R PP  
1 0 0 E

**Distributor:** Colorhouse

519 NE Hancock #B

Portland, OR 97212

1-800-535-5053 **emergency phone**

(503) 493-8275 **other calls**

(503) 232-0445 **fax phone**

## 2 - HAZARDS IDENTIFICATION

No reportable hazardous ingredients.

**Emergency overview:** May cause eye or skin irritation. May cause respiratory tract irritation.

**Routes of entry:** Eye and skin contact, ingestion, inhalation.

### Potential acute health effects:

**Eyes:** Direct contact may cause eye irritation, redness, and tearing.

**Skin:** Prolonged contact may cause transient reddening of the skin.

**Ingestion:** May cause gastrointestinal irritation, nausea, vomiting, or diarrhea.

**Inhalation:** Exposure to high vapor concentration may irritate mucous membranes and respiratory tract. Extreme overexposure may produce dizziness, headache, and nausea.

**Chronic health hazards:** Available information provides no evidence of chronic or delayed health hazards associated with exposure to this product.

**Medical conditions generally aggravated by exposure:** Pre-existing eye, skin, and respiratory system disorders, and unusual allergic sensitivity.

**Carcinogenicity:** OSHA: No ACGIH: No NTP: No IARC: No PROP 65: No

### 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Non-reportable ingredients, all products:

Component	CAS No.	Component	CAS No.
Water	07732-18-5	Modified Polyether	Proprietary
Acrylic resin	Proprietary	Kaolin	1332-58-7
Nepheline Syenite	37244-96-5	Styrene/Acrylic Copolymer	Proprietary
Calcined Kaolin	66402-68-4	Magnesium Silicate	14807-96-6
Barium Sulfate	7727-43-7		

NOTE: Potential unusual allergic sensitivity to trace ingredients of this product can be minimized by following recommended procedures for safe handling, storage, disposal, and use.

---

### 4 - FIRST AID MEASURES

**Eyes:** Flush eyes with fresh water for at least 15 minutes.

**Skin:** Wash thoroughly with soap and water.

**Ingestion:** Have victim drink enough fresh water to ensure dilution.

**Inhalation:** Move victim to fresh air.

**Notes to first aid providers:** Call for emergency medical care if symptoms persist.

---

### 5 - FIRE FIGHTING MEASURES

**Flammable limits in air (% by volume):** Upper: Not applicable. Lower: Not applicable.

**Flash point:** Not applicable.

**Autoignition temperature:** Not applicable.

**HMIS hazard classification:** Health: 1 Flammability: 0 Reactivity: 0 Protection: E

**Extinguishing media:** Foam, alcohol foam, CO<sub>2</sub>, dry chemical, water fog.

**Special fire fighting procedures:** Use self-contained breathing apparatus in confined spaces. Observe recommended procedures for handling ordinary combustible materials.

**Unusual fire and explosion hazards:** Liquid material is non-combustible, but dried films are capable of supporting combustion when in contact with open flames. Closed containers can develop internal pressure and may rupture when subjected to extreme heat.

**Hazardous decomposition products:** Combustion can produce carbon monoxide and/or carbon dioxide.

---

### 6 - ACCIDENTAL RELEASE MEASURES

Dike and absorb spilled liquid with inert material such as clay granules, sand, earth, or sawdust. Use rags to clean up small amounts of liquid spilled.

---

### 7 - HANDLING AND STORAGE

**Handling and storage:** Keep containers closed when not in use. Do not handle or store near heat, flame, or strong oxidizers, acids and alkalis. Store in cool, well-ventilated area rotate stock, use older material first. DO NOT FREEZE.

**Other precautions:** Inspect all containers for leaks periodically.

---

### 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering controls:** Use signs or barriers to restrict access to painting work area.

**Ventilation:** Normal air circulation should be sufficient. Otherwise, use portable fans.

**Respiratory protection:** For spray application, use particulate filter mask to avoid breathing spray mist. Exposed persons with unusual allergic sensitivity may need organic vapor respirator (NIOSH/MSHA TC 23C or equivalent).

**Eye protection:** Use safety glasses, goggles, or face shield to protect eyes.

**Skin protection:** Use waterproof gloves (latex, vinyl, rubber, or neoprene) to avoid skin contact.

**Other protective clothing or equipment:** Waterproof head covering and general protective clothing are recommended for protection as necessary.

**Work hygienic practices:** Wash hands and face before eating or drinking.

## 9 - PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Opaque liquid dispersion

**Physical state:** Liquid

**Boiling point:** 212°F, 100°C

**Vapor pressure:** Same as water vapor

**Specific gravity (H<sub>2</sub>O = 1):** 1.4

**Solubility in water:** partly soluble

**Percent volatile:** 60-65% by volume, 43-49% by weight

**Odor:** Very mild odor

**pH as supplied:** 8.5 - 9.0

**Freezing point:** 32°F, 0°C

**Vapor density:** Same as water vapor

**Evaporation rate:** Same as water

**Percent solids:** 35-40% by volume, 51-57% by weight

**Maximum volatile organic compound (VOC) content:**

**With water:** 1 gram per liter (0.0083 pound per gallon)

**Without water:** 2 grams per liter (0.0167 pound per gallon)

---

## 10 - STABILITY AND REACTIVITY

**Stability:** Stable.

**Conditions to avoid (stability):** Avoid storage or use at temperatures below 40°F.

**Incompatibility (materials to avoid):** Avoid water-reactive materials, strong oxidizers, acids and alkalis.

**Hazardous decomposition products:** Combustion can produce carbon monoxide and/or carbon dioxide.

**Hazardous polymerization:** Will not occur.

---

## 11 - TOXOLOGICAL INFORMATION

No information available.

---

## 12 - ECOLOGICAL INFORMATION

No information available.

---

## 13 - DISPOSAL CONSIDERATIONS

**Waste disposal method:** Collect spilled material and contaminated absorbent material and rags into a suitable container and dispose in accordance with all applicable local, state, and federal regulations.

**RCRA hazard class:** Non-hazardous

---

## 14 - TRANSPORTATION INFORMATION

This product is not subject to DOT, IATA/ICAO, or IMO/IMDG transportation regulations. Acceptable for air transport as non-hazardous goods.

---

## 15 - REGULATORY INFORMATION (not meant to be all inclusive)

**U.S. federal regulations:**

**TSCA:** All components are listed in TSCA inventory or exempt.

**CERCLA:** Not listed as a hazardous substance.

**SARA title III:** Not listed as a hazardous substance.

**311/312 hazard categories:** Not applicable.

**313 reportable ingredients:** Not applicable.

**State regulations:** Not applicable.

**International regulations:** Not applicable.

---

## 16 - OTHER INFORMATION

**Other information:** Do not store in areas subject to freezing temperatures. Keep above 40°F at all times. Use only with adequate ventilation or protection. Avoid breathing spray mist or vapor. Do not ingest. Avoid contact with eyes and skin. Close container after each use. Keep out of reach of children.

**Preparer information:** YOLO Colorhouse, LLC; 503-493-8275 (phone) Date: 6/6/2014

**Disclaimer:** The information conveyed above, although obtained from sources we consider reliable, is furnished by YOLO Colorhouse, LLC, without any warranty (whether express or implied) as to its accuracy, adequacy, or applicability to any particular needs or circumstances.

**MATERIAL SAFETY DATA SHEET – SC 3100 Series 50 VOC**

**PRODUCT NAME:** DECK & DOCK  
**PRODUCT CODE:** SC-3101-SC-3104

**HMIS CODES:** H<sub>1</sub> F<sub>0</sub> R<sub>0</sub> P<sub>B</sub>  
**D.O.T. CLASS:** NOT REGULATED

**SECTION I - MANUFACTURER IDENTIFICATION**

**MANUFACTURER'S NAME:** DUCKBACK PRODUCTS, INC.  
**ADDRESS:** P.O. BOX 980, 2644 HEGAN LANE, CHICO, CA 95927  
**EMERGENCY PHONE:** CHEM TEL (24 HOUR) (800) 255-3924 **DATE PRINTED:** 05/18/2011  
**INFORMATION PHONE:** (800) 825-5382 **PREPARED BY:** DUCKBACK PRODUCTS

**SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION**

<b>REPORTABLE COMPONENTS:</b>	<b>ACGIH TLV / TWA</b>	<b>CAS NUMBER</b>	<b>VAPOR PRESSURE mm Hg @ TEMP</b>	<b>WEIGHT PERCENT</b>
PROPYLENE GLYCOL	NA	57-55-6	<1 @ 25°C	< 2

\* CHEMICAL (S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III AND OF 40 CFR 372. THIS INFORMATION MUST BE INCLUDED IN ALL MSDS'S THAT ARE COPIED AND DISTRIBUTED FOR THIS MATERIAL.

**\*\*WARNING:** THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

**SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS**

**FLAMMABLE LIMITS IN AIR BY VOLUME-** LOWER: N/A UPPER: N/A  
**FLASH POINT:** NONE METHOD USED: N/A  
**BOILING RANGE:** 212 DEG F SPECIFIC GRAVITY (H2O=1): 1.25  
**VAPOR DENSITY:** HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER  
**COATING V.O.C.:** <50 GRAMS/LITER MATERIAL V.O.C.: <20 GRAMS/LITER  
**SOLUBILITY IN WATER:** COMPLETE DENSITY: 10.43 LB / GAL  
**APPEARANCE:** VARIES DEPENDING ON COLOR ODOR: SLIGHT ODOR

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

**EXTINGUISHING MEDIA:** USE WATER FOG, FOAM, DRY CHEMICAL, OR CO2.  
**SPECIAL FIRE FIGHTING PROCEDURES:** MATERIAL IS NOT CONSIDERED A FIRE HAZARD. USE STANDARD FIRE FIGHTING TECHNIQUES TO EXTINGUISH FIRES INVOLVING THIS MATERIAL.  
**UNUSUAL FIRE AND EXPLOSION PROCEDURES:** MATERIAL DOES NOT CONTRIBUTE TO ANY UNUSUAL HAZARDS WHEN INVOLVED IN A FIRE. AS IN ANY FIRE, PREVENT, HUMAN EXPOSURE TO FIRE, SMOKE, FUMES, OR PRODUCTS OF COMBUSTION.

**SECTION V - REACTIVITY DATA**

**STABILITY:** STABLE  
**CONDITIONS TO AVOID:** KEEP FROM FREEZING. AVOID EXTREME HEAT, POOR VENTILATION, CORROSIVE ATMOSPHERES, AND EXCESSIVE AGING.  
**INCOMPATIBILITY:** (MATERIALS TO AVOID): ALKALINE MATERIAL, STRONG ACIDS, AND OXIDIZING MATERIALS.  
**HAZARDOUS DECOMPOSITION OR BYPRODUCTS:** CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN  
**HAZARDOUS POLYMERIZATION:** WILL NOT OCCUR



## **SECTION VI - ACUTE & CHRONIC HEALTH HAZARDS**

**INHALATION:** OVEREXPOSURE TO VAPORS MAY CAUSE DIZZINESS, BREATHING DIFFICULTY, HEADACHES AND LOSS OF COORDINATION.

**EYE CONTACT:** MAY CAUSE BURNING. IN CASE OF CONTACT, FLUSH EYES WITH PLENTY OF WATER.

**SKIN CONTACT:** LIQUID MAY BE SLIGHTLY IRRITATING TO THE SKIN.

**INGESTION:** INGESTION OF PRODUCT CAN CAUSE GASTROINTESTINAL IRRITATION, VOMITING, NAUSEA, AND DIARRHEA.

**SIGNS & SYMPTOMS:** EFFECTS OF OVEREXPOSURE MAY INCLUDE IRRITATION OF THE NOSE AND THROAT, IRRITATION OF THE DIGESTIVE TRACT AND SIGNS OF NERVOUS SYSTEM DEPRESSION INCLUDING HEADACHE, DROWSINESS, DIZZINESS, LOSS OF COORDINATION AND FATIGUE.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:** THERE IS NO DATA AVAILABLE WHICH ADDRESS MEDICAL CONDITIONS WHICH ARE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

**CARCINOGENICITY:** NTP CARCINOGEN: **NO** IARC MONOGRAPHS: **NO** OSHA REGULATED: **NO**

## **SECTION VII - FIRST AID MEASURES**

**INHALATION:** MOVE PERSON TO FRESH AIR. IF BREATHING STOPS, APPLY ARTIFICIAL RESPIRATION AND SEEK MEDICAL ATTENTION.

**EYE:** FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN AND GET MEDICAL ATTENTION IF ANY IRRITATION PERSISTS.

**SKIN:** WASH THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND WASH BEFORE RE-USE.

**INGESTION:** DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY.

## **SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** PROVIDE GOOD VENTILATION, DIKE SPILL AREA AND ADD SUITABLE ABSORBENT TO SPILLED LIQUID, PLACE ABSORBED MATERIAL INTO A SEALED METAL CONTAINER FOR PROPER DISPOSAL.

**WASTE DISPOSAL METHOD:** DO NOT CONTAMINATE WATER, FOOD, OR FEED BY STORAGE OR DISPOSAL. DISPOSE OF EMPTY CONTAINERS AND ABSORBED SPILL MATERIALS AND ANY UNUSED PRODUCT IN ACCORDANCE WITH ALL LOCAL, STATE, AND FEDERAL REGULATIONS.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** WEAR PROTECTIVE CLOTHING WHEN USING. USE IN WELL VENTILATED AREA. STORE IN COOL, DRY, WELL-VENTILATED AREA. EXERCISE DUE CAUTION TO PREVENT DAMAGE TO THE CONTAINER. KEEP CONTAINER TIGHTLY SEALED WHEN NOT IN USE. PROTECT FROM FREEZING.

**OTHER PRECAUTIONS:** NONE

## **SECTION IX - CONTROL MEASURES**

**RESPIRATORY PROTECTION:** WEAR A VAPOR / MIST RESPIRATOR (NIOSH / MSHA TC 23C OR EQUIVALENT) DURING SPRAY APPLICATIONS OR WHEN VENTILATION IS INADEQUATE TO PREVENT INHALATION OVEREXPOSURE.

**VENTILATION:** GENERAL MECHANICAL VENTILATION OR LOCAL EXHAUST SHOULD BE ADEQUATE TO PREVENT OVEREXPOSURE.

**PROTECTIVE GLOVES:** USE IMPERMEABLE CHEMICAL HANDLING GLOVES FOR SKIN PROTECTION.

**EYE PROTECTION:** USE CHEMICAL SAFETY GLASSES, GOGGLES, OR FACE SHIELD FOR EYE PROTECTION.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** USE IMPERMEABLE APRONS AND PROTECTIVE CLOTHING WHENEVER POSSIBLE TO PREVENT SKIN CONTACT.

**WORK / HYGIENIC PRACTICES** WHEN USING PRODUCT DO NOT EAT, DRINK, OR SMOKE. WASH HANDS THOROUGHLY AFTER USING.

## **SECTION X - DISCLAIMER**

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE, OBTAINED FROM SOURCES BELIEVED BY DUCKBACK PRODUCTS, INC. TO BE ACCURATE, BUT IS FURNISHED WITHOUT ANY EXPRESSED OR IMPLIED WARRANTIES.

